

CLAIMS

1. A greening structure comprising a plant-cultivable planting portion on a water-reserving portion and laid on a pavement for forming a greening area,

wherein the improvement comprises post-shaped members provided substantially consecutively from a portion where an external force loaded on said planting portion is directly received, to the bottom of said water-reserving portion or to said pavement, so that said external force is received on said pavement through said post-shaped members.

2. A greening structure according to claim 1,

wherein said substantially consecutive post-shaped members include: first post-shaped members disposed upward from the bottom of said planting portion; and second post-shaped members disposed downward from the bottom of said planting portion.

3. A greening structure according to claim 2, further comprising:

a retaining structure for retaining the vicinity of the bottom of said water-reserving portion and the vicinities of the lower ends of said second post-shaped members.

4. A greening structure according to claim 1,

wherein said substantially consecutive post-shaped members are erected upward from the bottom face of said

water-reserving portion to the portion where said external force is directly received.

5. A greening structure according to claim 1, wherein said substantially consecutive post-shaped members include: first post-shaped members erected upward from the bottom of said planting portion; and second post-shaped members erected upward from the bottom of said water-reserving portion.

6. A greening structure according to claim 5, further comprising:

a retaining structure for retaining the vicinity of the bottom of said planting portion and the vicinities of the top ends of said second post-shaped members.

7. A greening structure according to claim 1, 2, 3, 4, 5 or 6,

wherein said substantially consecutive post-shaped members, said first post-shaped members or said second post-shaped members have no hollow portion.